



**ARCHITECTURAL SPECIFICATION**  
**CRI Fixed Corner Guards**

*[NOTE TO SPECIFIER, SELECT PRODUCT MODEL DEPENDING ON DESIRED FINISH]*

**SECTION 10 26 00 – Wall and Door Protection**  
**SECTION 10 26 13 – Corner Guards**  
**SECTION 10 26 23 – Protective Wall Covering**  
**SECTION 10 26 23.13 – Impact Resistant Wall Protection**

**PART I – GENERAL**

**1.01 SECTION INCLUDES**

- A. This section covers the furnishing and installation of CRI Fixed Corner Guards.
- B. For further information, contact Alvarado at +1 909.591.8431, or email [information@alvaradomfg.com](mailto:information@alvaradomfg.com).

**1.02 QUALITY ASSURANCE**

- A. Manufacturer shall be a company specializing in the supply of asset protection products with a minimum of 10 years' experience.
- B. Installer shall have a minimum of three years' of experience installing similar equipment, or shall supply a factory-trained supervisor during installation of the CRI Fixed Corner Guards.

**1.03 SUBMITTALS**

- A. Submit manufacturer's descriptive literature for specified equipment, including options.
- B. Provide dimensional layout and installation instructions.
- C. Provide shop drawings, if required.

**1.04 DELIVERY, STORAGE AND HANDLING**

- A. Deliver materials to job site in manufacturer's packaging undamaged, complete with installation instructions.
- B. Store off ground, under cover, protected from weather, construction activities and debris.
- C. Use forklift, pallet jack or equivalent equipment for moving.

**1.05 PROJECT/SITE CONDITIONS**

Install the CRI Fixed Corner Guard on a level floor.

**1.06 WARRANTY**

Alvarado Manufacturing Co., Inc. warrants the CRI Fixed Corner Guard from defects in material or workmanship, for the period of ONE YEAR from date of shipment. Complete details of the warranty are available from Alvarado by request

**PART II – PRODUCTS**

**2.01 MANUFACTURER**

Alvarado Mfg. Co., Inc. 12660 Colony Street, Chino, CA 91710.

**2.02 PRODUCT**

The CRI Fixed Corner Guard, no substitutions.

**2.03 CONSTRUCTION**

- A. CRI: 7-gauge cold-rolled steel.

## **2.04 EQUIPMENT**

- A. General: The CRI Fixed Corner Guard is designed to provide corner protection for cases and walls.
- B. Dimensions: Standard width: 8.5". Standard heights include: 12", 16", and 24".

## **2.05 FINISHES**

- A. Polished Chrome: The CRI Fixed Corner Guard is fabricated from 7-gauge cold-rolled steel with a polished chrome.

## **2.06 FACTORY TESTING**

- A. Product shall be fully tested at the factory to ensure proper functionality.
- B. Inspect product finish. Touch up prior to shipment.

## **PART III – EXECUTION**

### **3.01 SITE EXAMINATION**

- A. Inspection: Installer must examine the installation location and advise the contractor of any site conditions inconsistent with proper installation of the product. Installation shall not begin until unacceptable conditions are rectified. These conditions include but are not limited to the following:
  - 1. Product must be installed on level concrete.
- B. Installation: The installer should perform the installation, in consultation with the owner or end user, following the practices and installation guidelines that come with the product.
- C. Cleaning: Clean metal surfaces carefully after installation to remove excess caulk, dirt and labels.

**Note: This specification includes recommended options. Alvarado Mfg. Co., Inc. reserves the right to change this specification at any time without notice.**