

Technical Specifications

SL-10 Gate



Dimensions	Unit Height:	35" (890mm)	*Post shown are not included with the SI
	Unit Width:	47.5" (1207mm)	
	Gate Arm Width:	36" (914mm)	
Function	A double sleeve hinge assembly and flip latch enables the SL-10 to swing in either direction and be mounted on any new or existing 2.25" OD post.		
Materials	<u>Gate Arm</u>	The Gate Arm is made from two (2 tubes welded to a 0.25" x 2" steel p notched and welded center rod rein OD steel rings are welded on one the gate to slide onto an existing h lined with plastic rings to reduce me ID steel flip latch is bolted to the (installation for latch is required).	plate at each end. A 0.75" OD forces the arm. Two (2) 2.75" end of the gate arm to allow inge post. Each hinge ring is etal on metal contact. A 2.34"
	<u>Hinge Rings</u>	Two (2) steel Hinge Rings are provi on existing hinge post. Each Hinge with two set screws. The Hinge Ring diameter than the hinges on the Ga scrape against the Gate Arm as it m	Ring is secured to the post gs are slightly smaller in te Arm, so that they do not
	Fiber Washers	Two (2) Fiber Washers are provided hinges from the hinge rings. They a by preventing metal on metal contact	llow the Gate Arm to rotate
Available Finishes	Chrome Plated	All external materials are plated with	h a bright chrome finish.
Weight	Approximately 13 lbs. (5.89 kg)		
Shipping Details	Each SL-10 Gate is shipped in a single package that includes both the Gate Arm and hardware to mount the gate to an existing post. Alvarado ships products throughout the world		
Installation Details	All SL-10 Gates must be attached to an existing or newly installed post. Installation should be performed by a skilled installer following the manufacturer's instructions (included).		
Warranty	Alvarado Manufacturing Co., Inc. warrants the SL-10 Gate from defects in material or workmanship, for the period of one (1) year from the date of shipment. Complete details of the warranty are available from Alvarado by request.		