protecting assets and controlling the flow of people

FP Rope Stanchion



Technical Specifications

Dimensions	Unit Height:	36” (914mm)
	Base Width:	12.75” (324mm)
Function	The FP Stanchion is a portable rope stanchion capable of supporting ropes up to 6’ in length.	
Materials	Post	The post is a 2’” OD tube made from 16-gauge cold rolled steel. A 4” OD four-way rope flange made of 11-gauge cold rolled steel is welded to the top. The flange has four (4) holes to attach ropes to the post.
	Base Cover and Weight	The base cover is made of stamped 4-gauge cold rolled steel. The base weight is made of cast iron with a weight of 17 lbs.
Available Finishes	Chrome Plated	All external fabricated materials are plated with a bright chrome finish.
	Brass Plated	All external fabricated materials are plated with a brass finish.
Weight	Approximately 18.5 lbs. (8.39 kg).	
Shipping Details	The FP Stanchion is shipped ready for assembly. Alvarado ships products throughout the world.	
Installation Details	All FP Stanchion must be installed on level concrete. Installation should be performed by a skilled installer following the manufacturer’s instructions (included).	

Options

Ropes
Numerous styles and colors are available.

Rope Ends
The Rope Ends are available in hook and snap styles.

Warranty	Alvarado Manufacturing Co., Inc. warrants the FP Stanchion from defects in material or workmanship, for the period of one (1) year from the date of shipment. Complete details of the warranty are available from Alvarado by request.